10/605,263

Filed:

5

September 18, 2003

Page 2 of 9

Examiner: John C. Hong Group Art Unit: 3726

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

## Listing of Claims:

 (Original) An automated manufacturing line for making a composite article from first and second thermoformed workpieces by automatically assembling the first thermoformed workpiece to the second thermoformed workpiece, comprising:

a thermoforming station for thermoforming the first and second thermoformed workpieces in a plastic sheet;

a trim station for trimming at least the first thermoformed workpiece from the plastic sheet; and

an assembly station for assembling the first thermoformed workpiece onto the second thermoformed workpiece to form the composite article.

- 2. (Original) The automated manufacturing line according to claim 1 wherein the assembly station assembles the first thermoformed workpiece to the second thermoformed workpiece by press-fitting the first and second thermoformed workpieces.
- (Original) The automated manufacturing line according to claim 2 wherein the pressfitting of the first and second thermoformed workpieces is a snap-fit.
- 4. (Original) The automated manufacturing line according to claim 1 wherein the assembly station assembles the first thermoformed workpiece to the second thermoformed workpiece by an adhesive coupling.
- 5. (Original) The automated manufacturing line according to claim 1 wherein the assembly station assembles the first thermoformed workpiece to the second thermoformed workpiece by an ultrasonic weld.

10/605,263

Filed:

September 18, 2003

Examiner: John C. Hong Group Art Unit: 3726

Page 3 of 9

6. (Original) The automated manufacturing line according to claim 1 wherein the assembly station comprises a carrier moveable between a first position, where it picks the first thermoformed workpiece, and a second position, where it assembles the first thermoformed workpiece to the second thermoformed workpiece.

- 7. (Original) The automated manufacturing line according to claim 6 wherein the carrier comprises a suction device to pick the first thermoformed workpiece as it is trimmed from the sheet and hold the first thermoformed workpiece as it is carried to the second thermoformed workpiece.
- 8. (Original) The automated manufacturing line according to claim 7 wherein the carrier comprises a force reliever to control the amount of force applied by the carrier to the first and second thermoformed workpieces as they are assembled.
- (Original) The automated manufacturing line according to claim 8 wherein the carrier comprises a reciprocating arm on an end of which the suction device is mounted.
- 10. (Original) The automated manufacturing line according to claim 9 wherein the force reliever mounts the suction device to the end of the arm.
- 11. (Original) The automated manufacturing line according to claim 9 wherein the reciprocating arm reciprocates between a pick-up position that corresponds to the first position, and an assembly position that corresponds to the second position.
- 12. (Original) The automated manufacturing line according to claim 11 wherein the reciprocating arm reciprocates between the pick-up and assembly positions in a direction that is either parallel or transverse to the machine direction as defined by the movement of the plastic sheet through the assembly station.

Examiner: John C. Hong

Group Art Unit: 3726

Serial No.

10/605,263

Filed:

5

5

September 18, 2003

Page 4 of 9

13. (Original) The automated manufacturing line according to claim 11 wherein the trim station comprises a first punch and die set for trimming the first thermoformed workpiece from the plastic sheet.

- 14. (Original) The automated manufacturing line according to claim 13 wherein the die comprises an inlet opening in which the punch is received to trim the first thermoformed workpiece from the plastic sheet when the plastic sheet is positioned between the punch and die, and an outlet opening into which the reciprocating arm extends to pick up the first thermoformed workpiece when the reciprocating arm is in the pick-up position.
- 15. (Original) The automated manufacturing line according to claim 14 wherein the assembly station further comprises a moveable platform carrying the reciprocating arm and which is moveable between a first position where the reciprocating arm is positioned within the die outlet, and a second position where the reciprocating arm is positioned outside of the die outlet.
- 16. (Original) The automated manufacturing line according to claim 15 wherein there are multiple reciprocating arms, with at least one of the arms at the pick-up position when another of the arms is at the assembly position providing for the contemporaneous pick-up of a first thermoformed workpiece while a previously pick-up first thermoformed workpiece is being assembled to the second thermoformed workpiece.
- 17. (Original) The automated manufacturing line according to claim 16 wherein the trim station further comprises a second punch and die set for trimming the assembled first and second thermoformed workpieces from the plastic sheet.
- 18. (Original) The automated manufacturing line according to claim 6 wherein there are multiple carriers.
- 19. (Original) The automated manufacturing line according to claim 18 wherein the multiple carriers are arranged in at least two sets, wherein when one of the at least two sets is in the first position, the other of the at least two sets is in the second position providing for the

10/605,263

Filed:

5

September 18, 2003

Page 5 of 9

Examiner: John C. Hong Group Art Unit: 3726

contemporaneous pick-up of a first thermoformed workpiece while a previously pick-up first thermoformed workpiece is being assembled to the second thermoformed workpiece.

- 20. (Original) The automated manufacturing line according to claim 6 wherein the movement of the carriers between the first and second positions is either generally parallel or transverse to the machine direction as defined by the movement of the plastic sheet through the assembly station.
- 21. (Original) The automated manufacturing line according to claim 6 wherein the trim station comprises a first punch and die set for trimming the first thermoformed workpiece from the plastic sheet.
- 22. (Original) The automated manufacturing line according to claim 21 wherein the die comprises an inlet opening in which the punch is received to trim the first thermoformed workpiece from the plastic sheet when the plastic sheet is positioned between the punch and die, and an outlet opening into which the carrier extends to pick up the first thermoformed workpiece.
- 23. (Original) The automated manufacturing line according to claim 21 wherein the trim station further comprises a second punch and die set for trimming the assembled first and second thermoformed workpieces from the plastic sheet.
- 24. (Original) The automated manufacturing line according to claim 1 wherein the assembly station moves the first thermoformed workpiece directly from the trim station onto the second thermoformed workpiece eliminating the need to temporarily store the first thermoformed workpiece prior to assembly to the second thermoformed workpiece.
- 25. (Original) An apparatus for automatically forming a composite article by assembling first and second workpieces thermoformed in a common plastic sheet comprising a plurality of the first and second work pieces, the assembly station comprising:

a trimmer for trimming at least one of the first workpieces from the plastic sheet; and

10/605,263

Filed:

5

September 18, 2003

Examiner: John C. Hong Group Art Unit: 3726

Page 6 of 9

a carrier moveable between a first position, where the carrier picks up one of the first workpieces, and a second position, where the carrier assembles the first workpiece to one of the second workpieces in the plastic sheet.

- 26. (Original) The apparatus according to claim 25 wherein the carrier moves directly between the first and second positions eliminating the need to temporarily store the first workpiece prior to assembly to the one of the second workpieces.
- 27. (Original) The apparatus according to claim 26 wherein the carrier assembles the first workpiece to the one of the second workpieces by a press-fit coupling.
- 28. The apparatus according to claim 27 wherein the carrier comprises a suction device to pick the first workpiece as it is trimmed from the sheet and to hold the first workpiece as it is assembled to the second workpiece.
- 29. (Original) The apparatus according to claim 28 wherein the carrier comprises a force reliever to control the amount of force applied by the carrier to the second workpiece during the assembly of the first workpiece to the second workpiece.
- 30. (Original) The apparatus according to claim 29 wherein the carrier comprises a reciprocating arm on an end of which the suction device is mounted.
- 31. (Original) The apparatus according to claim 30 wherein the force reliever mounts the suction device to the end of the arm.
- 32. (Original) The apparatus according to claim 31 wherein the reciprocating arm reciprocates between a pick-up position that corresponds to the first position, and an assembly position that corresponds to the second position.
- 33. (Original) The apparatus according to claim 32 wherein the reciprocating arm reciprocates between the pick-up and assembly positions in a direction that is either parallel or

10/605,263

Filed:

5

September 18, 2003

Page 7 of 9

Examiner: John C. Hong Group Art Unit: 3726

transverse to the machine direction as defined by the movement of the plastic sheet through the assembly station.

- (Original) The apparatus according to claim 33 wherein the trimmer comprises a first 34. punch and die set for trimming the first workpiece from the plastic sheet.
- (Original) The apparatus according to claim 34 wherein the die comprises an inlet 35. opening in which the punch is received to trim the first workpiece from the plastic sheet when the plastic sheet is positioned between the punch and die, and an outlet opening into which the reciprocating arm extends to pick up the first workpiece when the reciprocating arm is in the pick-up position.
- (Original) The apparatus according to claim 35 wherein the assembly station further 36. comprises a moveable platform carrying the reciprocating arm and which is moveable between a first position where the reciprocating arm is positioned within the die outlet, and a second position where the reciprocating arm is positioned outside of the die outlet.
- (Original) The apparatus according to claim 36 wherein there are multiple reciprocating 37. arms, with at least one of the arms at the pick-up position when another of the arms is at the assembly position.
- (Original) The apparatus according to claim 37 and further comprising a second trimmer 38. having a second punch and die set for trimming the assembled first and second workpieces from the plastic sheet.
- (Original) The apparatus according to claim 25 wherein there are multiple carriers, with 39. each carrier picking up a different first workpiece in the first position and assembling it to a different second workpiece.
- (Original) The apparatus according to claim 25 wherein the carrier assembles the first 40. workpiece to the second workpiece by a press-fit coupling.

10/605,263

Filed:

September 18, 2003

Examiner: John C. Hong Group Art Unit: 3726

Page 8 of 9

41. (Original) The apparatus according to claim 40 wherein the press-fit coupling is a snap-fit coupling.

- 42. (Original) The apparatus according to claim 25 wherein the assembly station assembles the first workpiece to the second workpiece by an adhesive coupling.
- 43. (Original) The apparatus according to claim 25 wherein the assembly station assembles the first workpiece to the second workpiece by an ultrasonic weld.

44-81. (Cancelled)